





Proliftix[®] Electric

Adjustable Height Tables



Fits the most popular spaces, with over 20 sizes available



Quickly adjust height from 27 1/4" to 43 1/4"



Secondary surface lift allows a separate keyboarding area



Nine laminates options to complement any office

Sit or Stand at Work With Ease

With a height-adjustable table, standing is as simple as sitting. The Proliftix electric tables provide an economical sit-to-stand solution for today's diverse workforce. Worksurfaces are available in four popular shapes and over 20 sizes, with 9 laminate options. There's a solution for virtually every office.

Value Features

- Ease of use - Quickly adjust the table height at 1.7" per second using the simple up/down control switch.
- Protection - Your investment is protected with our limited lifetime warranty and a 5 year warranty on the motor and controls.
- Flexibility - Quickly change out crossbar stretchers for base-only installations as your needs change.
- Strength - Generous table base lift capacity of 300 lbs. supports the equipment needs of today's computer-intensive work environments.

Style Features

- Plan for any office configuration – big or small, with a variety of work surface shapes and sizes.
- Create a distinct look in your office with a broad selection of laminates and paints.


Additional Range

For extended reach, select a bi-level worksurface with 22 1/4" - 50 1/4" height range, exceeding ANSI/BIFMA 5th - 95th percentile requirements.

Idea at Work provides office ergonomic products that offer superior value, performance and reliability.

Proliftix Electric — Adjustable Height Tables

Rectangular




- Adjusts from 27 1/4" - 43 1/4" at 1.5" per second
- Two leg table
- 300 lbs. load capacity

Nominal
Dimensions

W	D	Model #	Laminate ¹	Edge	Weight
36	24	TKEB3624		- 02	88
42	24	TKEB4224		- 02	93
48	24	TKEB4824		- 02	99
60	24	TKEB6024		- 02	111
72	24	TKEB7224		- 02	122
36	30	TKEB3630		- 02	88
42	30	TKEB4230		- 02	93
48	30	TKEB4830		- 02	99
60	30	TKEB6030		- 02	111
72	30	TKEB7230		- 02	122


Rectangular - Bi-level



- Adjusts from 27 1/4" - 43 1/4" at 1.5" per second
- Front surface 12" height range with +/- 15° tilt
- Two leg table
- 300 lbs. load capacity

30	36	TKEB3035B		- 02	141
36	36	TKEB3635B		- 02	149
48	36	TKEB4835B		- 02	166


Equal Corner - 2 Legs



- Adjusts from 27 1/4" - 43 1/4" at 1.5" per second
- Two leg table
- 300 lbs. load capacity

W/L	W/R	D	Model #	Laminate ¹	Edge	Weight
42	42	24	TKEB424224		- 02	108
45	45	24	TKEB454524		- 02	113
48	48	24	TKEB484824		- 02	118
48	48	30	TKEB484830		- 02	123

Equal Corner - 2 legs, Bi-level



- Adjusts from 27 1/4" - 43 1/4" at 1.5" per second
- Front surface 12" height range with +/- 15° tilt
- Two leg table
- 300 lbs. load capacity

42	42	24	TKEB424224B		- 02	153
45	45	24	TKEB454524B		- 02	158
48	48	24	TKEB484824B		- 02	164
48	48	30	TKEB484830B		- 02	174

TO ORDER SPECIFY

- 1) Model, width & depth of work surface (eg TKEB4824)
 - 2) Laminate (eg SG241)
 - 3) Edge Treatment (eg 02)
- Example: TKEB4824-SG241-02

Notes:

1. For available laminates and edge treatment, please see separate Color and Trim Options see Color and Trim Options in the Idea at Work Pricing & Specification Guide.
2. Paint finish is Black only
3. For base-only configurations, only the model # is required (eg TKEB4824)
4. **Note, dimensions provided above are nominal.** Actual widths of all tables are reduced by 2" and depths by 1". For example, a nominal 48" x 24" rectangular table has an actual dimension of 46" x 23".

5. Dual Surface specifications: Front surface adjusted using Brutus (ATK50) arm with +5/8", -6 1/2" height range and +/- 15° tilt range. Front surface laminate and trim matches main work surface.
6. Work surfaces are pre-drilled with mounting location for bases and dual surface platform (if any). Work surfaces are pre-drilled for RH switch location
7. All tables and bases ship unassembled. Weight information is shipped weight for base only.
8. Control box powered by 120V / 60Hz. May draw 3 amps maximum under full load, idle current is typically 20mA. 10ft grounded power cord.
9. Moving work surfaces can collide with other components. Installation of overhead storage or wall mounted accessories in worksurface's path not recommended.
10. 300 lbs. load capacity is for table base only.
11. To add tool bars and accessories which move with the work surface and can accept a variety of desk accessories, see the Proxi Accessories Cut Sheet.

The following are federally registered trademarks of Workrite Ergonomics: Workrite Ergonomics®, Proliftix®. The following is a trademark of Workrite Ergonomics: Idea at Work™.



Printed with 25% post-consumer waste, 50% total recycled content.
1400106-0408 ©2008 Contents subject to change without notice.

Idea at Work
1450 Technology Lane
Petaluma, CA 94954
www.idea-at-work.com
800.959.9675

